



PGM DIESEL CH-4

Description

PGM Diesel CH-4 heavy-duty diesel engine oil is developed for severe service in high-output diesel engines, either naturally aspirated or super-charged. It minimizes deposits, reduces wear and imparts dispersant and detergent properties. It is formulated from high VI paraffin base oils and chemical additives to provide optimum control of deposits in severe service and control against wear, rust and corrosion.

Application

PGM Diesel CH-4 is recommended for use in high output diesel engines in commercial vehicles where manufacturer's specifications require API CH-4 performance level oil.

Benefits

- Very strong detergent and dispersant SHPD oil
- Good control over deposits at high temperatures.
- Excellent protection against bore polishing
- Extended oil drain interval
- Eliminates seasonal oil changes.
- High TBN value to neutralise acids.
- Especially recommended for new generation turbo engines
- Reduces oil consumption.

Performance Level: API CH-4

PGM DIESEL CH-4

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE Grade	–	20W50	
Viscosity @ 100 °C	mm ² /s	14.5	ASTM D-445
Viscosity Index	–	125	ASTM D-2270
Flash Point, COC	°C	230	ASTM D-92
Base Number	mg KOH/g	11	ASTM D-2896

NOTE: The test data shown in this table are recent average values and are subject to usual tolerance

Pak Grease Manufacturing Co. (Pvt.) Ltd.

6, Oil Installation Area, Keamari, Karachi - 75620, Pakistan.

Off. : 021 32851628, 021 32850523, Fax : +92 21 32856382,

Email : mgmt@pakgrease.com.pk, Website : www.pakgrease.com.pk

