



## PGM DIESEL CF-4

### Description

**PGM Diesel CF-4** heavy-duty diesel engine oil is developed for severe service in high-output diesel engines, either naturally aspirated or super-charged. It minimizes deposits, reduces wear and imparts dispersant and detergent properties. It is formulated from high VI paraffin base oils and chemical additives to provide optimum control of deposits in severe service and control against wear, rust and corrosion.

### Application

**PGM Diesel CF-4** is recommended for use in high output diesel engines in commercial vehicles where manufacturer's specifications require API CF-4 performance level oil.

### Benefits

- Good control over deposits at high temperatures.
- Improved fuel economy.
- Good control over low temperature sludge.
- Eliminates seasonal oil changes.
- Reduces oil consumption.

**Performance Level:** API CF-4/SG

## PGM DIESEL CF-4

PROPERTIES	UNITS	VALUE	TEST METHOD
SAE Grade	–	20W50	
Viscosity @ 100 °C	mm <sup>2</sup> /s	20	ASTM D-445
Viscosity Index	–	125	ASTM D-2270
Flash Point, COC	°C	230	ASTM D-92
Pour Point	°C	-4	ASTM D-97
Base Number	mg KOH/g	8	ASTM D-2896

**NOTE:** The test data shown in this table are recent average values and are subject to usual tolerance

**Pak Grease Manufacturing Co. (Pvt.) Ltd.**

6, Oil Installation Area, Keamari, Karachi - 75620, Pakistan.

Off. : 021 32851628, 021 32850523, Fax : +92 21 32856382,

Email : mgmt@pakgrease.com.pk, Website : www.pakgrease.com.pk

